



GRAISSE 3790

Marine grease

Description

Totally insoluble in cold, hot or sea water as well as in steam these properties enable to use it for lubrication of immersed or under severe water spray working equipment's. Highly adhesive and stringy.

Applications

For all parts subject to water projection or immersed ; Bearings, rollers, pumps, valves and taps. Water purification plants, hydroelectric power stations, canneries, etc.

Technical data

Operating temperature range: -30°C to +140°C

NLGI Grade: 2

Load: 315 kg

| Reference | designation | Packaging | | | | food certificate number |
|-----------|--|-----------|----|-----------|--------------|-------------------------|
| 379050 | ADHESIVE GREAS E-NLGI2-GRAISSE 3790-KEG 50KG | TONNELET | | KEG | 50 KG | |
| 37905L | ADHESIVE GREAS E-NLGI2-GRAISSE 3790-BUCKET 5L | CARTON | 2 | BUCKET | 5 L | |
| 3790A2 | ADHESIVE GREAS E-NLGI2-GRAISSE 3790-AEROSOL 650/400ML | CARTON | 12 | AEROSOL | 650 / 400 ML | |
| 3790B1 | ADHESIVE GREAS E-NLGI2-GRAISSE 3790-TIN 1L | CARTON | 6 | TIN | 1 L | |
| 3790CA | ADHESIVE GREAS E-NLGI2-GRAISSE 3790-CARTRIDGE 400GR | CARTON | 24 | CARTRIDGE | 400 G | |

