

AIR S22 AL

Oil for FRL circuit, MOSH / MOAH / POSH free

Description

For a clean lubrication operation of compressed air tools, pumps and compressed air appliances. Better performance for mechanisms. Approved by 2probity.eu, in category H1 Registration CA1824301.

Applications

Lubrication of all compressed air circuits and protection of pumps, compressed air tools and appliances operating with compressed air in all moist, dusty, corrosive and hot conditions.

Technical data

Operating temperature range: -20°C to +150°C
Viscosity @ 40°C: 22 cst
MPR > 80%

Reference	designation	Packaging				food certificate number
AIRS22ALB1	COMPRESSED AIR OIL-FOOD GRADE-ECOFRIENDLY-AIR S22 AL-CAN 1L	CARTON	12	CAN	1 L	CA1824301
AIRS22AL5L	COMPRESSED AIR OIL-FOOD GRADE-ECOFRIENDLY-AIR S22 AL-JERRYCAN 5L	CARTON	2	CAN	5 L	
AIRS22ALFL	COMPRESSED AIR OIL-FOOD GRADE-ECOFRIENDLY-AIR S22 AL-BOTTLE 250ML	CARTON	12	BOTTLE	250 ML	

The information contained in this document is given in good faith and does not engage our responsability. To know more, pleas check the safety data sheet